

<u>MATERIAL:</u>	3.0mm MARINE GRADE ALUMINIUM.
<u>FINISH:</u>	TO BE POWDER COATED COLORBOND WILDERNESS GREEN.
<u>HINGES:</u>	GRADE 316 STAINLESS STEEL HINGES & PINS WITH LOCKING WASHERS UNDER FIXING SCREWS.
<u>HANDLES:</u>	TO BE SUPPLIED BY CLIENT REQUIRE 3 POINT LOCKING SYSTEM WITH ROLLER ENDS TO BE SUPPLIED BY MANUFACTURER ON DOORS. ALL LOCKS ARE 5Y3.
<u>GEAR PLATES:</u>	CONTROL & DISTRIBUTION GEAR TRAY - 1020mm HIGH x 910mm WIDE TELEMETRY GEAR TRAY - 620mm HIGH x 880mm WIDE INSTRUMENT GEAR TRAY - 400mm HIGH x 400mm WIDE TO BE POWDER COATED WHITE & FRONT OF GEAR TRAY TO BE 25mm FROM WALL.
<u>ESCUTCHEON DOORS:</u>	TO BE POWDER COATED WHITE & HAVE M4 CHROMED, SLOTTED ROUND HEAD THUMB SCREWS WITH RETAINING CLIP (2 PLACES). TO BE FITTED WITH CABLE SUPPORT RAILS MOUNTED BEHIND.
<u>EXTERNAL VENTS:</u>	B & R EXTERNAL VENT KIT IPVX SUPPLIED WITH GASKET, INSERT FILTER & FIXINGS OR EQUIVALENT.
<u>PLINTH:</u>	ALUMINIUM PREFORMED CHANNEL CONSTRUCTED IN ONE CONTINUOUS LENGTH.
<u>DOOR SEALS:</u>	5060 PVC / NITRILE 6mm THICK OR EQUIVALENT.
<u>DOOR STAYS:</u>	ALL EXTERNAL DOORS TO BE FITTED WITH MECHANICALLY LOCKING ROD TYPE DOOR STAYS TO KEEP DOOR OPEN AT A MINIMUM OF 110 DEGREES.
<u>CABLE SUPPORTS:</u>	10 x 25 CABLE SUPPORT RAILS TO BE MOUNTED ON SIDE OF CABINET'S INTERIOR & ESCUTCHEON AS SHOWN.



DESIGNED BY:

[illegible]